



# WL2 Firewall® Tall

Excellent purifying performance,  
easy operation, and stylish design

## Purified water for your organization

With a choice of hot and cold, the WL2 Firewall Tall is the preferred solution for any small or medium-sized workplace, looking for great-tasting water, reliability, and guaranteed quality.

## Advanced technology

The WL2 FW Tall features three core technologies:



### High performance filtration

The WL2 FW Tall features reverse osmosis filtration for the reduction of lead, asbestos, and cysts to give you the best possible filtration.



### Firewall purification

Waterlogic's patented Firewall® technology features a highly effective UVC purification system that acts all the way through to the point of dispense. **Firewall® guarantees water free from viruses and bacteria up to 99.9999%. Guaranteed effective against COVID-19.**



### BioCote® protection\*

The key plastic surfaces, surrounding the dispensing area, are infused with BioCote®, a silver ion additive that provides an effective barrier against microbes like bacteria and mold, which may cause odors or staining.

## Certified purity for peace of mind

The Firewall technology has been certified by IAPMO R&T to NSF/ANSI-55 Class A UV and NSF P231 protocol, which is unique – **no other water cooler features these standards of certification together.** This means that **Firewall technology delivers the safest water** possible for the workplace.



\*BioCote® technology does not protect users or others against disease causing bacteria, germs, viruses or other harmful organisms. This technology is not a substitute for good hygiene and/or cleaning practices. BioCote® has not been tested or proven effective against SARS-CoV-2.

## Features

Firewall®, patented UVC technology, reduces the risks of viruses, cysts, and pathogenic bacteria, purifying the water up to 99.9999%, 100% of the time

BioCote® reduces microbes up to 99.5% within 2 hours

Generous drip tray capacity for collecting accidental spillage

LED UV fault indicator for easier servicing and peace of mind

Dispensing area suitable to accommodate sport bottles

Ready for hands-free pedal retrofit

Hot water safety double press via manually operated button or via hot pedal

## Water options

cold

hot



## Technical specifications

### Types available

Freestanding

### Dimensions

Freestanding

13.74" (W) x 46.3" (H) x 14.3" (D)

### Dispensing area height

9"

### Weight

Freestanding: ~58 lbs

### Standard filtration supplied

Four-stage reverse osmosis filtration with a two-gallon bladder tank

### Storage capacity

Hot tank: 0.4 gal

Cold tank (Freestanding): 1.06 gal

### Drip tray capacity

12.70 fl oz

### Compressor

Compressor (R134a) 120V/60Hz

### Water temperature settings

Cold: 37°F / 41°F / 45°F (default set at 41°F)

Hot: 185-189°F (default set at 189°F)

Number of users 10-30

## Contact us today

Waterlogic Americas  
[www.waterlogicsusa.com](http://www.waterlogicsusa.com)  
(855) 350-5518  
[info@waterlogicsusa.com](mailto:info@waterlogicsusa.com)

3175 Bass Pro Drive,  
Grapevine, TX 76051

## Tested and certified



Firewall technology is certified IAPMO R&T to **NSF/ANSI 55 Class A, NSF P231, US EPA, NSF/ANSI 372 and CSA B483.1.**



\*certificate may vary depending on different models or products